



Test Report No.: FM2012WDG0026

RF EXPOSURE REPORT

Applicant	Particle Industries, Inc
Address	126 Post St, 4th floor, San Francisco, CA 94108 USA



Manufacturer or Supplier	Particle Industries, Inc
Address	126 Post St, 4th floor, San Francisco, CA 94108 USA
Product	Boron 2G/3G
Brand Name	Particle
Model	BRN310
Additional Model & Model Difference	BRN314
Date of tests	Sep. 03, 2018 ~ Nov. 08, 2018

FCC Part 2 (Section 2.1091)

KDB 447498 D01

IEEE C95.1

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Breeze Jiang Senior Project Engineer / EMC Department	Approved by Glyn He Assistant Manager / EMC Department
	 Date: Dec. 28, 2020

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942, People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION	5
5. TARGET POWER AND TOLERANCE	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	7
7. CONCLUSION OF SIMULTANEOUS TRANSMITTER.....	7



Test Report No.: FM2012WDG0026

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM180831N010	Original release	Dec. 10, 2018
FM2012WDG0026	Based on the original report FM180831N010 changed the brand name and added the additional model, but it doesn't need to be retested.	Dec. 28, 2020

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com

1. CERTIFICATION

FCC ID:	2AEMI-BRN310
PRODUCT:	Boron 2G/3G
BRAND NAME:	Particle
MODEL NO.:	BRN310
ADDITIONAL NO.:	BRN314
TEST SAMPLE:	Engineering Sample
APPLICANT:	Particle Industries, Inc
STANDARDS:	FCC Part 2 (Section 2.1091)
	KDB 447498 D01
	IEEE C95.1

Note: Additional model BRN314 is identical with the test model BRN310 except the model name for trading purpose.

2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$Pd = (Pout * G) / (4 * pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

5. TARGET POWER AND TOLERANCE

<u>Technology/Band</u>	<u>Mode</u>	<u>Target Power and Tolerance (dBm)</u>
GSM 850	GSM (GMSK, 1Tx-slot)	32±1.0 dBm
	GPRS (GMSK, 1Tx-slot)	32±1.0 dBm
	GPRS (GMSK, 2Tx-slot)	31±1.0 dBm
	GPRS (GMSK, 3Tx-slot)	29±1.0 dBm
	GPRS (GMSK, 4Tx-slot)	28±1.0 dBm
	EDGE (8PSK, 1Tx-slot)	26±1.0 dBm
	EDGE (8PSK, 2Tx-slot)	23±1.0 dBm
	EDGE (8PSK, 3Tx-slot)	22±1.0 dBm
	EDGE (8PSK, 4Tx-slot)	20±1.0 dBm
GSM 1900	GSM (GMSK, 1Tx-slot)	29±1.0 dBm
	GPRS (GMSK, 1Tx-slot)	29±1.0 dBm
	GPRS (GMSK, 2Tx-slot)	28±1.0 dBm
	GPRS (GMSK, 3Tx-slot)	26±1.0 dBm
	GPRS (GMSK, 4Tx-slot)	25±1.0 dBm
	EDGE (8PSK, 1Tx-slot)	25±1.0 dBm
	EDGE (8PSK, 2Tx-slot)	23±1.0 dBm
	EDGE (8PSK, 3Tx-slot)	21±1.0 dBm
	EDGE (8PSK, 4Tx-slot)	19±1.0 dBm
WCDMA Band II	RMC 12.2K	21±1.0 dBm
WCDMA Band V	RMC 12.2K	22±1.0 dBm
DSSS(802.15.4)	OQPSK	-1±1.0 dBm



6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

Band	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)	Power Density / Limit
GSM 850 (1 Tx slot)	1.0	33.0	34.000	2.512	316.228	0.063	0.549	0.115
GPRS 850 (1 Tx slot)	1.0	33.0	34.000	2.512	316.228	0.063	0.549	0.115
GPRS 850 (2 Tx slots)	1.0	32.0	33.000	1.995	501.187	0.100	0.549	0.182
GPRS 850 (3 Tx slots)	1.0	30.0	31.000	1.259	472.063	0.094	0.549	0.171
GPRS 850 (4 Tx slots)	1.0	29.0	30.000	1.000	501.187	0.100	0.549	0.182
EGPRS 850 (1 Tx slot)	1.0	27.0	28.000	0.631	79.433	0.016	0.549	0.029
EGPRS 850 (2 Tx slots)	1.0	24.0	25.000	0.316	79.433	0.016	0.549	0.029
EGPRS 850 (3 Tx slots)	1.0	23.0	24.000	0.251	94.189	0.019	0.549	0.034
EGPRS 850 (4 Tx slots)	1.0	21.0	22.000	0.158	79.433	0.016	0.549	0.029
GSM 1900 (1 Tx slot)	3.5	30.0	33.500	2.239	281.838	0.056	1.000	0.056
GPRS 1900 (1 Tx slot)	3.5	30.0	33.500	2.239	281.838	0.056	1.000	0.056
GPRS 1900 (2 Tx slots)	3.5	29.0	32.500	1.778	446.684	0.089	1.000	0.089
GPRS 1900 (3 Tx slots)	3.5	27.0	30.500	1.122	420.727	0.084	1.000	0.084
GPRS 1900 (4 Tx slots)	3.5	26.0	29.500	0.891	446.684	0.089	1.000	0.089
EGPRS 1900 (1 Tx slot)	3.5	26.0	29.500	0.891	112.202	0.022	1.000	0.022
EGPRS 1900 (2 Tx slots)	3.5	24.0	27.500	0.562	141.254	0.028	1.000	0.028
EGPRS 1900 (3 Tx slots)	3.5	22.0	25.500	0.355	133.045	0.026	1.000	0.026
EGPRS 1900 (4 Tx slots)	3.5	20.0	23.500	0.224	112.202	0.022	1.000	0.022
WCDMA Band 5	1.0	23.0	24.000	0.251	251.189	0.050	0.551	0.091
WCDMA Band 2	3.5	22.0	25.500	0.355	354.813	0.071	1.000	0.071
DSSS(802.15.4)	0	0	0	0.001	-	0.000199	1.000	0.000199

7. CONCLUSION OF SIMULTANEOUS TRANSMITTER

Both of the WLAN and plug-in device can transmit simultaneously, the formula of calculated the MPE is:

$$CPD1/LPD1+CPD2/LPD2+.....etc. < 1$$

CPD = Calculation power density

LPD = Limit of power density



Test Report No.: FM2012WDG0026

Therefore the worst-case situation is $0.182+0.000199 = 0.182199$, which is less than "1", This confirmed that the device comply with FCC 1.1310 MPE limit.

--- END ---